

ITA 14

PLASTIC STRAPPING TOOL > PNEUMATIC

Pneumatic Strapping Tool for 25mm / 32mm Polypropylene & Polyester Strap

ITA 14 is the heavy duty pneumatic plastic strapping tool.

Strong, powerful and reliable, ITA 14 represent the most suitable pneumatic plastic strapping tool, studied for 25mm and 32mm PET strap.

Generating up to 6000 N tension force ITA 14 finds application in all heavy duty applications where the highest tension is needed, like even in steel, aluminium, hardwood timber and all other materials, using high strength Polyester Strap

Easy to be used, ITA 14 is powerful, quick and strong.

ITA 14 is manufactured to be durable and with very low maintenance required.

TECHNICAL SPECIFICATION	
Dimensions	300 x 160 x 175 mm
Weight	5.8 Kg
STRAP	
Туре	PET Strap
Width	25mm / 32mm
Thickness	0,8mm - 1,27mm

POWER SUPPLY	
Pressure Range	6 - 7 bar / 87-99 psi
Air Consumption	14 l/s - 29cuft/min
PERFORMANCE	
Max. tension force	5000 N - 6.5 bar - 92 psi 6000 N - 6.5 bar - 92 psi
Tensioning speed	6 mt/min (5000N version) 4 mt/min (6000N version)
Sealing	Friction weld seal
Joint Strenght	75% of breaking strenght *



FEATURES

Strong and Reliable
Easy to be used
Durable and low maintenance required
Suspension hook already equipped

BENEFITS

Adjustable tension
Powerful and Robust
Friction weld and high seal efficiency
Heavy duty applications (coils, ferrous and non ferrous industries, etc)

MODEL		
CODE	DESCRIPTION	
T142533	ITA 12 - for 25mm PET strap - 5000N	
T149953	ITA 14 - for 25/32 mm PET strap - 6000N	