










# ErgoPack - Productrange

1

	 <b>Xpert Line</b>				<b>The Benchmark in Ergonomic Pallet Strapping</b>					 <b>Economy Line</b>				
Model	700X	713X	726X	745X	700	700E	713E	726E	745E					
														
Power	235W	235W	235W	235W	-	93W	93W	93W	93W					
Drive	Electric motor with <b>reinforced angle gear</b> , electronically controlled				manually via a hand crank	Electric motor with <b>spur gear</b> , electronically controlled								
Battery Pack	3 x 12V AGM Battery	3 x 12V AGM Battery	3 x 12V AGM Battery	3 x 12V AGM Battery	-	2 x 12V AGM Battery	2 x 12V AGM Battery	2 x 12V AGM Battery	2 x 12V AGM Battery					
Operating Voltage	36V	36V	36V	36V	-	24V	24V	24V	24V					
Strapping cycles per battery charge (standard strapping*)	650	650	650	650	-	350	350	350	350					
Charger	36V Charger, 4,5A	36V Charger, 4,5A	36V Charger, 4,5A	36V Charger, 4,5A	-	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A	2 x 12V Dual Charger, 2A					
Chain speed	66m/min	66m/min	66m/min	66m/min	-	40m/min	40m/min	40m/min	40m/min					
Pallets width setting	via Siemens Industrial Touchscreen in 10cm steps, works with work gloves				mechanically, by inserting a bolt in the appropriate position in 20cm steps									
Other settings	individual setting options via the Siemens Industrial Touchscreen, such as: <ul style="list-style-type: none"> <li>• chain speed,</li> <li>• chain length,</li> <li>• standby timer,</li> <li>• strap lifter time for upper position,</li> <li>• Line Laser on / off,</li> <li>• Sealing Head on / off</li> </ul>				-	-	-	-	-					
Indicators	<ul style="list-style-type: none"> <li>• charging level indicated graphically and in %,</li> <li>• set pallet width,</li> <li>• permanent graphically indication of the ChainLance position,</li> <li>• strapping cycles,</li> <li>• sliding window open graphically and in writing,</li> <li>• safety instructions,</li> <li>• menu-driven step by step description for semi automated strap roll change</li> </ul>				-	3 LEDs indicating charging level and sliding window „open“								
Software update	easy update via USB stick				-	only by manufacturer								

standard equipment

Model	700X	713X	726X	745X	700	700E	713E	726E	745E
									
AGR-Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓
ChainLance				special, glass fiber reinforced, high strength soft-slide chain					
Tool-Lift	-	✓	✓	✓	-	-	✓	✓	✓
Sealing Head	-	✓	✓	✓	-	-	✓	✓	✓
Tension Force	-	150N – 1200N	400N – 2500N	400N – 4500N	-	-	150N – 1200N	400N – 2500N	400N – 4500N
Strap Types	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET	PP/PET
Strap Width	9–25mm	9–13mm	12–16mm	15–19mm	9–25mm	9–25mm	9–13mm	12–16mm	15–19mm
Strap Thickness	0,5–1,3mm	0,35–0,85mm	0,5–1,0mm	0,8–1,3mm	0,5–1,3mm	0,5–1,3mm	0,35–0,85mm	0,5–1,0mm	0,8–1,3mm
Triplex-Tool-Lift	-	✓	✓	✓	-	-	✓	✓	✓
Sealing Head removable	-	✓	✓	✓	-	-	✓	✓	✓
Line Laser	✓	✓	✓	✓	-	✓	✓	✓	✓
Strap Brake Relief	✓	✓	✓	✓	✓	✓	✓	✓	✓
Reversing Sledge	47 / 47S	47 / 47S	47 / 47S	47 / 47S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S	47 / 47S / 85S
Header with Bumper	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Overheight Module	✓	✓	✓	✓	-	✓	✓	✓	✓
Stationary Sledge Tunnel	✓	✓	✓	✓	-	✓	✓	✓	✓
Mobile Sledge Tunnel Station	✓	✓	✓	✓	-	✓	✓	✓	✓
Ergonomic battery change trolley	✓	✓	✓	✓	-	✓	✓	✓	✓

## \* Standard strapping:

Battery pack: 100 charging- and discharging-cycles | Strap: 13 mm PET (complete strap roll) | Sealing Tool: 726, Tension Force 900 N without soft, Welding time 2 | Pallet: pallet width 0.8 m, pallet height 1.15 m | Strapping speed: fast | Room temperature: 20 °C