

EVO 16-19

PLASTIC STRAPPING TOOL > BATTERY

Battery Strapping Tool for 16mm / 19mm PP & PET Strap Opening Lever free Bluetooth connection & Mobile APP

ITA EVO HT is the INNOVATIVE and REVOLUTIONARY battery strapping tool, studied for 16mm and 19mm PP and PET strap .

Lightweight, well balanced, ergonomic and easy to be used, ITA EVO can works in three different operating modes (fully automatic, semi-automatic and manual).

ITA EVO have been developed without the standard opening lever for a more comfortable strapping operation.

With the integrated Bluetooth connection it will be possible set, check and update the tool, directly with your mobile devices (APP available for Android and iOS systems).

ITA EVO ave been developed with Brushless motors that allow a very fast strapping operation, granting also low maintenance, and improved electronic control.

Equipped with high efficiency and long life Li-lons battery, You can reach even more than 400 cycles per charge, without any memory effect

Thanks also to the Soft Tensioning Mode, ITA EVO can be used in any application field, from timber to logistic, from steel to brick industry and much more.

| TECHNICAL SPECIFICATION | | |
|-------------------------|------------------------------|--|
| Dimensions | 330 x 140 x 142 mm | |
| Weight (with battery) | 4,6 Kg | |
| STRAP | | |
| Туре | PP and PET Strap | |
| Width | 16mm / 19mm (0.06" - 0.075") | |
| Thickness | 0,7mm - 1,3mm (0.028"-0.05") | |
| Tensile Strength | 850 - 1100 N/mm² | |
| POWER SUPPLY | | |
| Battery | Li-lon - 18V - 5Ah | |
| PERFORMANCE | | |
| Tension force | 900 - 4500 N | |
| Tensioning speed | 6 mt/m | |
| Sealing | Friction weld seal | |

75% of breaking strength*

*variable according to strap type

Joint strength



EVOLUTION & REVOLUTION

Opening lever free
Bluetooth connection
Dedicated mobile APP
Digital control Panel
Very fast in tensioning and welding

FEATURES

3 Operating Modes:
Automatic / Semi Automatic / Manual
High Capacity 18V Li-Ion Battery
Soft & Standard Tensioning

BENEFITS

Wide range & adjustable tension (900N-4500N)

Easy to be used

Ergonomic design & perfectly balanced

Friction weld and high seal efficiency

Strong and well protected motor housing

| MODEL | |
|----------|--|
| CODE | DESCRIPTION |
| T2999971 | ITA EVO HT + 1 Battery + 1 Battery Charger |
| T2999972 | ITA EVO HT + 2 Batteries + 1 Battery Charger |
| T2999973 | ITA EVO HT + 3 Batteries + 1 Battery Charger |